



Package Code 2

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				Impellimax		
	Rev	Number	Date	By	OUTLINE		
	A	ECO 1851	3/17/99	PC			
B	ECO 2096	11/13/00	PC	Sheet 1 of 2			
Information herein is believed accurate. Suitability not guaranteed.				Drawn By: RWW	Date: 11/13/00	Approved:	
				DRF:	Date: 10/29/93	P.C.	
						Drawing # 9619-50	

PIN	CONNECTION	PIN	CONNECTION
1	-5V	14	NC
2	Output 1	13	Output 2
3	Ground	12	NC
4	NC	11	NC
5	NC	10	NC
6	Input 1	9	Input 2
7	+5v	8	NC

Notes:

- 1) Inputs are TTL compatible.
- 2) Outputs are independent and inverting. Output current is +/- 25 mA nominal, +/-20 mA minimum, at +/-5V into a 39 ohm resistor. Outputs provide current spikes.
- 3) Switching speed is 8 nsec typical into a resistive load.
- 4) Unit contains internal .01 bypass caps on supplies.

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>			
	Rev	Number	Date	By	OUTLINE			
Information herein is believed accurate. Suitability not guaranteed.	A	ECO 1851	3/17/99	PC				Drawn By: RWW
	B	ECO 2096	11/13/00	PC	DRF:		Date: 10/29/93	Drawing # 9619-50
					Approved:		P.C.	