



<p>Tolerances Except as Noted</p> <p>.x = +/- .05 .xx = +/- .01 .xxx = +/- .005</p> <p>Dimensions in inches</p>	Revisions				<u>Impellimax</u>		
	A	ECO	2/19/91	P.C.	OUTLINE		
B	ECO 2056	6/28/00	P.C.	Sheet 1 of 2			
<p>Information herein is believed accurate. Suitability not guaranteed.</p>					<p>Drawn By: P. C.</p>	<p>Date: 11/28/90</p>	<p>Drawing # GS3-50</p>
					<p>DRF: -</p>	<p>Approved: P. C.</p>	

PIN	CONNECTION	PIN	CONNECTION
1	-5 V to -18V	22	NC
2	NC	21	Out 1 NI
3	Rset	20	Out 1 Inv
4	Ground	19	Out 2 NI
5	In 1	18	Out 2 Inv
6	In 2	17	Out 3 NI
7	In 3	16	Out 3 Inv
8	NC	15	NC
9	NC	14	NC
10	NC	13	NC
11	+5V	12	-V Int

Notes:

- 1) Channels are independent and TTL compatible. Logic "0" is defined as 0.8 V max, logic "1" is 1.4 to 5 V max. Logic low TTL current is 0.5 mA max.
- 2) Noninverting outputs are at ground for TTL hi, and inverting outputs are at negative.
- 3) Switching speed is 30 nsec typical.
- 4) Unit contains internal .01 uF bypass capacitors.
- 5) Connect resistor (in the range of 2K to 10K) from Rset (pin 3) to -V (pin 1) to set negative output voltage. Alternatively, apply -5 to -8 V directly to - V Int (pin 12).

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>		
	A	ECO	2/19/91	P.C.	OUTLINE		
B	ECO 2056	6/28/00	P.C.				
Information herein is believed accurate. Suitability not guaranteed.						Sheet 2 of 2	
				Drawn By: P. C.	Date: 11/28/90	Drawing #	
				DRF: -	Approved: P. C.	GS3-50	