



<p>Tolerances Except as Noted</p> <p>.x = +/- .05 .xx = +/- .01 .xxx = +/- .005</p> <p>Dimensions in inches</p>	Revisions				<u>Impellimax</u>	
	A	ECO 2126	02/12/01	P.C.	OUTLINE	
<p>Information herein is believed accurate. Suitability not guaranteed.</p>						Sheet 1 of 2
					<p>Drawn By: J.P.</p> <p>DRF: NA</p>	<p>Date: 10/22/93</p> <p>Approved: P.C.</p>
						Drawing # NS4-53

PIN	CONNECTION	PIN	CONNECTION
1	+ 5 V	22	NC
2	Input 1	21	NC
3	Output 1	20	NC
4	Input 2	19	NC
5	Output 2	18	NC
6	Input 3	17	NC
7	Output 3	16	NC
8	Input 4	15	NC
9	Output 4	14	NC
10	- 5 to - 30V	13	NC
11	Ground	12	NC

Notes:

- 1) Switching speed is 200 nsec typical into 1N914 loads.
- 2) Unit contains internal .01 bypass caps on both supplies. Supplies are not reverse bias protected.
- 3) Channels are independent TTL compatible and noninverting.

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>	
	A	ECO 2126	02/12/01	P.C.	OUTLINE	
Information herein is believed accurate. Suitability not guaranteed.						Sheet 2 of 2
					Drawn By: J. P.	Date: 10/22/93
				DRF: NA	Approved: P. C.	Drawing # NS4-53